

RoHS Compliant Product  
A suffix of "-C" specifies halogen & lead-free

## FEATURES



- Planar MOS Schottky technology
- Low forward voltage drop
- High current capability
- High reliability
- High surge current capability
- Epitaxial construction

## MECHANICAL DATA

- Case: Molded plastic
- Epoxy: UL94V-0 rate flame retardant
- Lead: Lead solderable per MIL-STD-202 method 208 guaranteed
- Polarity: As Marked
- Mounting position: Any

## ORDER INFORMATION

Part Number	Type
SBL20A60	Lead (Pb)-free
SBL20A60-C	Lead (Pb)-free and Halogen-free



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	14.22	16.51	J	0.70	1.78
B	9.57	10.90	K	0.38	1.11
C	12.50	14.75	L	2.01	3.07
D	3.56	5.10	M	2.22	3.43
E	0.51	1.47	N	3.10	4.31
F	2.03	3.19	O	8.10	9.65
G	0.279	0.76	P	1.18 Typ.	
H	2.95	4.5			

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating 25°C ambient temperature unless otherwise specified. Single phase half wave, 60Hz, resistive or inductive load.  
For capacitive load, de-rate current by 20%.)

Parameter	Symbol	Rating	Unit
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	60	V
Working Peak Reverse Voltage	$V_{RSM}$	60	V
Maximum DC Blocking Voltage	$V_{DC}$	60	V
Maximum Average Forward Rectified Current	(Per Leg)	10	A
	(Per Device)	20	
Peak Forward Surge Current, 8.3 ms single half sine-wave Superimposed on rated load (JEDEC method)	$I_{FSM}$	120	A
Voltage Rate of Change (Rated $V_R$ )	$dv/dt$	10000	V / $\mu s$
Typical Thermal Resistance from Junction to Case	$R_{\theta JC}$	2	°C / W
Operating and Storage Temperature Range	$T_J, T_{STG}$	150, -55~150	°C

## ELECTRICAL CHARACTERISTICS


Parameter	Symbol	Typ.	Max.	Unit	Test Condition
Maximum Instantaneous Forward Voltage	$V_F$	0.45	0.49	V	$I_F=3A, T_J=25^\circ C$
		0.5	0.55		$I_F=5A, T_J=25^\circ C$
		0.6	0.65		$I_F=10A, T_J=25^\circ C$
		0.57	-		$I_F=10A, T_J=125^\circ C$
Maximum DC Reverse Current at Rated DC Blocking Voltage <sup>2</sup>	$I_R$	-	0.5	mA	$T_J=25^\circ C$
		-	20		$T_J=100^\circ C$
Typical Junction Capacitance <sup>1</sup>	$C_J$	280	-	pF	

Notes:


1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
2. Pulse Test : Pulse Width = 300  $\mu s$ , Duty Cycle  $\leq$  2.0%.

**RATINGS AND CHARACTERISTIC CURVES**


Typical Forward Current Derating Curve




Typical Forward Characteristic



Typical Junction Capacitance



Typical Reverse Characteristic



Maximum Non-Repetitive Forward Surge Current

