




RoHS Compliant Product
A suffix of "-C" specifies halogen & lead-free

FEATURES

- High Current Capability
- Extremely Low Thermal Resistance
- For Surface Mount Application
- Higher Temp Soldering : 250°C for 10 Seconds at Terminals
- Low Reverse Current

SMA



MECHANICAL DATA

- Case: Molded Plastic
- Epoxy: UL 94V-0 Rate Flame Retardant
- Lead: Axial Leads, Solderable per MIL-STD-202 method 208 Guaranteed
- Polarity: Color Band Denotes Cathode End
- Mounting Position: Any

PACKAGE INFORMATION

Package	MPQ	Leader Size
SMA	5K	13' inch

REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	1.25	1.65	E	0.051	0.203
B	3.99	4.60	F	4.78	5.28
C	2.50	2.90	G	0.76	1.52
D	1.98	2.44	H	0.152	0.305

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating 25°C ambient temperature unless otherwise specified. Single phase half wave, 60Hz, resistive or inductive load.
For capacitive load, de-rate current by 20%.)


Parameter	Symbol	Rating	Unit
Peak Repetitive Peak reverse voltage	V_{RRM}	200	V
Working Peak Reverse Voltage	V_{RWM}	200	V
Maximum DC Blocking Voltage	V_R	200	V
Average Forward Current @ $T_J=25^\circ\text{C}$	$I_{F(AV)}$	2	A
Peak Forward Current @ 8.3 ms Half Sine	I_{FSM}	50	A
Maximum Instantaneous Forward Voltage	V_F	$I_{FM} = 2.0 \text{ A}, T_A = 25^\circ\text{C}$	0.9
		$I_{FM} = 2.0 \text{ A}, T_A = 75^\circ\text{C}$	0.85
		$I_{FM} = 2.0 \text{ A}, T_A = 125^\circ\text{C}$	0.72
Maximum DC Reverse Current At Rated DC Blocking Voltage ⁴	I_R	$T_J = 25^\circ\text{C}$	0.2
		$T_J = 100^\circ\text{C}$	5
Typical Junction Capacitance ¹	C_J	70	pF
Typical Thermal Resistance ²	$R_{\theta JA}$	80	$^\circ\text{C} / \text{W}$
Typical Thermal Resistance ³	$R_{\theta JC}$	25	$^\circ\text{C} / \text{W}$
Voltage Rate of Change (Rated V_R)	dv / dt	10000	$\text{V} / \mu\text{s}$
Operating Temperature Range	T_J	-50~150	$^\circ\text{C}$
Storage temperature	T_{STG}	-65~150	$^\circ\text{C}$

Notes:


1. Measured at 1MHz and applied reverse voltage of 5.0 V D.C.
2. Thermal Resistance Junction to Ambient.
3. Thermal Resistance Junction to Case.
4. Pulse test: 300us pulse width, 1% duty cycle

RATINGS AND CHARACTERISTIC CURVES


Typical Forward Current Derating Curve




Typical Reverse Characteristic



Typical Junction Capacitance



Typical Forward Characteristic



Maximum Non- Repetitive Forward Surge Current

