


RoHS Compliant Product  
A suffix of "-C" specifies halogen free

## FEATURES


- Trench Barrier Schottky technology
- Low forward voltage drop
- Low reverse current
- High current capability
- High reliability
- High surge current capability
- Epitaxial construction

## MECHANICAL DATA

- Case: Molded plastic
- Epoxy: UL94V-0 rate flame retardant
- Lead: Lead solderable per MIL-STD-202 method 208 guaranteed
- Polarity: As Marked
- Mounting position: Any
- Weight: 1.98 g (Approximate)



ITO-220



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	14.60	15.70	H	2.70	4.00
B	9.50	10.50	J	0.90	1.50
C	12.60	14.00	K	0.50	0.90
D	4.30	4.70	L	2.34	2.74
E	2.30	3.2	M	2.40	3.00
F	2.30	2.90	N	∅3.0	∅3.4
G	0.30	0.75			

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating 25°C ambient temperature unless otherwise specified. Single phase half wave, 60Hz, resistive or inductive load. For capacitive load, de-rate current by 20%.)

Parameter	Symbol	Rating	Unit
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	120	V
Working Peak Reverse Voltage	$V_{RSM}$	120	V
Maximum DC Blocking Voltage	$V_{DC}$	120	V
Maximum Average Forward Rectified Current	$I_F$	10	A
(Per Leg)		20	
(Per Device)			
Peak Forward Surge Current, 8.3 ms single half sine-wave	$I_{FSM}$	150	A
Voltage Rate of Change (Rated $V_R$ )	$dv/dt$	10000	V / $\mu s$
Typical Thermal Resistance	$R_{\theta JC}$	4	°C / W
Operating and Storage Temperature Range	$T_J, T_{STG}$	-40~150	°C

## ELECTRICAL CHARACTERISTICS


Parameter	Symbol	Typ.	Max.	Unit	Test Condition
Maximum Instantaneous Forward Voltage	$V_F$	0.66	0.7	V	$I_F = 3A, T_J = 25^\circ C$
		0.71	0.75		$I_F = 5A, T_J = 25^\circ C$
		0.8	0.85		$I_F = 10A, T_J = 25^\circ C$
		0.65	-		$I_F = 10A, T_J = 125^\circ C$
Maximum DC Reverse Current at Rated DC Blocking Voltage <sup>2</sup>	$I_R$	-	0.1	mA	$T_J = 25^\circ C$
		-	10		$T_J = 100^\circ C$
Typical Junction Capacitance <sup>1</sup>	$C_J$	210	-	pF	

NOTES:


1. Measured at 1MHz and applied reverse voltage of 5.0V D.C.
2. Pulse Test : Pulse Width = 300  $\mu s$ , Duty Cycle  $\leq$  2.0%.

**RATINGS AND CHARACTERISTIC CURVES**


Typical Forward Current Derating Curve




Typical Forward Characteristic



Typical Junction Capacitance(pF)



Typical Reverse Characteristic



Maximum Non-Repetitive Forward Surge Current

