

RoHS Compliant Product  
A suffix of "-C" specifies halogen & lead-free

## DESCRIPTION



These miniature surface mount MOSFETs utilize a high cell density trench process to provide low  $R_{DS(on)}$  and to ensure minimal power loss and heat dissipation. Typical applications are DC-DC converters and power management in portable and battery-powered products such as computers, printers, PCMCIA cards, cellular and cordless telephones.

## FEATURES

- Low  $R_{DS(on)}$  provides higher efficiency and extends battery life.
- Low thermal impedance copper leadframe SOP-8PP saves board space.
- Fast switching speed.
- High performance trench technology.

## PACKAGE INFORMATION

Package	MPQ	Leader Size
SOP-8PP	3K	13 inch



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	0.85	1.00	$\theta$	0°	10°
B	5.3 BSC.		b	5.2 BCS	
C	0.15	0.25	c	0.30	0.50
D	3.8 BCS.		d	1.27 BSC	
E	6.05 BCS.		e	5.55 BCS	
F	0.03	0.30	f	0.10	0.40
G	4.35 BCS.		g	1.2 BCS.	
L	0.40	0.70			

## ABSOLUTE MAXIMUM RATINGS AND THERMAL DATA ( $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	$V_{DS}$	60	V
Gate-Source Voltage	$V_{GS}$	20	V
Continuous Drain Current <sup>1</sup>	$I_D$	6.4	A
		5.3	
Pulsed Drain Current <sup>2</sup>	$I_{DM}$	20	A
Continuous Source Current (Diode Conduction) <sup>1</sup>	$I_S$	2.3	A
Power Dissipation <sup>1</sup>	$P_D$	5.0	W
		3.2	
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 ~ 150	°C
Thermal Resistance Data			
Maximum Junction to Ambient <sup>1</sup>	$t \leq 10 \text{ sec}$	$R_{\theta JA}$	25
	Steady-State		65

Notes

1. Surface Mounted on 1" x 1" FR4 Board.
2. Pulse width limited by maximum junction temperature.

**ELECTRICAL CHARACTERISTICS** ( $T_A=25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test conditions
<b>Static</b>						
Gate-Threshold Voltage	$V_{GS(\text{th})}$	1	-	-	V	$V_{DS} = V_{GS}$ , $I_D = 250\mu\text{A}$
Gate-Body Leakage	$I_{GSS}$	-	-	100	nA	$V_{DS} = 0\text{V}$ , $V_{GS} = 12\text{V}$
Zero Gate Voltage Drain Current	$I_{DSS}$	-	-	1	$\mu\text{A}$	$V_{DS} = 48\text{V}$ , $V_{GS} = 0\text{V}$
		-	-	5		$V_{DS} = 48\text{V}$ , $V_{GS} = 0\text{V}$ , $T_J = 55^\circ\text{C}$
On-State Drain Current <sup>1</sup>	$I_{D(\text{ON})}$	40	-	-	A	$V_{DS} = 5\text{V}$ , $V_{GS} = 10\text{V}$
Drain-Source On-Resistance <sup>1</sup>	$R_{DS(\text{ON})}$	-	-	82	$\text{m}\Omega$	$V_{GS} = 10\text{V}$ , $I_D = 2\text{A}$
		-	-	115		$V_{GS} = 4.5\text{V}$ , $I_D = 2\text{A}$
Forward Transconductance <sup>1</sup>	$g_{FS}$	-	40	-	S	$V_{DS} = 15\text{V}$ , $I_D = 6\text{A}$
Diode Forward Voltage	$V_{SD}$	-	0.7	-	V	$I_S = 2.3\text{A}$ , $V_{GS} = 0\text{V}$
<b>Dynamic <sup>2</sup></b>						
Total Gate Charge	$Q_g$	-	15	-	nC	$I_D = 6\text{A}$ $V_{DS} = 15\text{V}$ $V_{GS} = 4.5\text{V}$
Gate-Source Charge	$Q_{gs}$	-	3	-		
Gate-Drain Charge	$Q_{gd}$	-	5	-		
Turn-On Delay Time	$T_{d(\text{ON})}$	-	15	-	nS	$I_D = 1\text{A}$ , $V_{DD} = 15\text{V}$ $V_{GEN} = 10\text{V}$ $R_L = 6\Omega$
Rise Time	$T_r$	-	10	-		
Turn-Off Delay Time	$T_{d(\text{OFF})}$	-	54	-		
Fall Time	$T_f$	-	26	-		

Notes

1. Pulse test : PW  $\leq$  300 us duty cycle  $\leq$  2%.
2. Guaranteed by design, not subject to production testing.