

RoHS Compliant Product
A suffix of "-C" specifies halogen and lead-free

DESCRIPTION

These miniature surface mount MOSFETs utilize a high cell density trench process to provide low $R_{DS(on)}$ and to ensure minimal power loss and heat dissipation.


FEATURES

- Low $R_{DS(on)}$ provides higher efficiency and extends battery life.
- Low thermal impedance copper leadframe TO-220P saves board space.
- Fast Switch Speed.
- High performance trench technology.


APPLICATION

DC-DC converters and power management in portable and battery-powered products such as computers, printers, PCMCIA cards, cellular and cordless telephones.

TO-220P



P-Channel



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	7.90	8.10	M	-	1.50
B	9.45	9.65	N	0.75	0.95
C	9.87	10.47	O	0.66	0.86
D	-	11.50	P	13.50	14.50
E	1.06	1.46	Q	2.44	3.44
F	2.60	3.00	R	3.50	3.70
G	6.30	6.70	S	1.15	1.45
H	8.35	8.75	T	4.30	4.70
I	14.7	15.3	U	-	2.7
J	1.60	Typ.	V	1.89	3.09
K	1.10	1.30	W	0.40	0.60
L	1.17	1.37	X	2.60	3.60

ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DS}	-60	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ¹	I_D	-90	A
Pulsed Drain Current ²	I_{DM}	-390	A
Continuous Source Current (Diode Conduction) ¹	I_S	-110	A
Power Dissipation ¹	P_D	300	W
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55~175	$^\circ\text{C}$
Thermal Resistance Rating			
Maximum Junction to Ambient ¹	$R_{\theta JA}$	62.5	$^\circ\text{C} / \text{W}$
Maximum Junction to Case	$R_{\theta JC}$	0.5	

Notes:

- 1 Package Limited.
- 2 Pulse width limited by maximum junction temperature.

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ C$ unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Teat Conditions
Static						
Gate-Threshold Voltage	$V_{GS(th)}$	-1	-	-	V	$V_{DS}=V_{GS}$, $I_D = -250\mu A$
Gate-Body Leakage	I_{GSS}	-	-	± 100	nA	$V_{DS}=0$, $V_{GS} = -20V$
Zero Gate Voltage Drain Current	I_{DSS}	-	-	-1	μA	$V_{DS} = -48V$, $V_{GS}=0$
		-	-	-25		$V_{DS} = -48V$, $V_{GS}=0$, $T_J=55^\circ C$
On-State Drain Current ¹	$I_{D(on)}$	-120	-	-	A	$V_{DS} = -5V$, $V_{GS} = -10V$
Drain-Source On-Resistance ¹	$R_{DS(ON)}$	-	-	12	m Ω	$V_{GS} = -10V$, $I_D = -2A$
		-	-	14		$V_{GS} = -4.5V$, $I_D = -2A$
Forward Transconductance ¹	g_{fs}	-	30	-	S	$V_{DS} = -15V$, $I_D = -2A$
Diode Forward Voltage	V_{SD}	-	-1.1	-	V	$I_S = -2A$, $V_{GS}=0$
Dynamic ²						
Total Gate Charge	Q_g	-	100	-	nC	$V_{DS} = -15V$, $V_{GS} = -4.5V$, $I_D = -2A$
Gate-Source Charge	Q_{gs}	-	30	-		
Gate-Drain Charge	Q_{gd}	-	40	-		
Turn-on Delay Time	$T_{d(on)}$	-	20	-	nS	$V_{DD} = -25V$, $V_{GEN} = -10V$, $R_L=25\Omega$, $I_D = -34A$
Rise Time	T_r	-	20	-		
Turn-off Delay Time	$T_{d(off)}$	-	300	-		
Fall Time	T_f	-	100	-		

Notes:

- 1 Pulse test : $PW \leq 300 \mu s$ duty cycle $\leq 2\%$.
- 2 Guaranteed by design, not subject to production testing.