

RoHS Compliant Product  
A suffix of "-C" specifies halogen-free and RoHS Compliant

## FEATURES

- Heatsink Structure
- Low Profile, Typical Thickness 0.8mm
- Moisture Sensitivity: Level 1, Per J-STD-020
- High Temperature Soldering Guaranteed: 260°C/10 Seconds

## MARKING

Part Number	SM220DT	SM230DT	SM240DT
Marking	PS22	PS23	PS24


## PACKAGE INFORMATION

Package	MPQ	Leader Size
SOD-123DT	3K	7 inch


## ORDER INFORMATION

Part Number	Type
SM220DT~SM240DT	Lead (Pb)-free
SM220DT-C~SM240DT-C	Lead (Pb)-free and Halogen-free

### SOD-123DT



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	2.9	3.1	F	0.85	1.05
B	1.9	2.1	G	0.6 REF.	
C	0.75	0.9	H	0.4	0.85
D	3.5	3.9	I	1.66 REF.	
E	0.1	0.25	J	1.3	1.7



## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T<sub>A</sub>=25°C unless otherwise specified)

Parameter	Symbol	Part Number			Unit
		SM220DT	SM230DT	SM240DT	
Maximum Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	20	30	40	V
Maximum RMS Voltage	V <sub>RMS</sub>	14	21	28	V
Maximum DC Blocking Voltage	V <sub>DC</sub>	20	30	40	V
Maximum Average Forward Rectified Current	I <sub>F</sub>	2			A
Peak Forward Surge Current @8.3ms Single Half Sine-Wave Superimposed on Rate Load	I <sub>FSM</sub>	50			A
Rating for Fusing (t<8.3ms)	I <sup>2</sup> t	10			A <sup>2</sup> S
Maximum Instantaneous Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =2A, T <sub>A</sub> =25°C	0.51		V
		I <sub>F</sub> =2A, T <sub>A</sub> =125°C	0.45		
Maximum DC Reverse Current @Rated DC Blocking Voltage	I <sub>R</sub>	T <sub>A</sub> =25°C	50		uA
		T <sub>A</sub> =125°C	10		mA
Typical Junction Capacitance	C <sub>J</sub>	115			pF
Typical Thermal Resistance from Junction-Ambient <sup>1</sup>	R <sub>θJA</sub>	60			°C/W
Typical Thermal Resistance from Junction-Case <sup>2</sup>	R <sub>θJC</sub>	28			
Typical Thermal Resistance from Junction-Lead <sup>1</sup>	R <sub>θJL</sub>	6			
Operating Junction and Storage Temperature	T <sub>J</sub> , T <sub>STG</sub>	-55~150			°C

Notes:

1. The thermal resistance from junction to ambient or lead, mounted on P.C.B with 5×5mm copper pads, 2 OZ, FR4 PCB.
2. The thermal resistance from junction to case, mounted on P.C.B with recommended copper pads, 2 OZ, FR4 PCB.

**CHARACTERISTIC CURVES**




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Instantaneous Forward




Figure 4. Typical Reverse Characteristics




Figure 5. Typical Junction Capacitance